



深圳市友创伟业科技有限公司

Shenzhen YCY Technology CO;LTD

---

## 锂聚合物(Li-Polymer)电芯型录

Version:02

日期: 2013/1/1

网址:[www.ycybattery.com](http://www.ycybattery.com)

电 话: +86-755-2957 7567 传 真: +86-755-2819 8212

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
1	YCY XX1148	061148	230	215	≤130	3.7	6.0	6.2	11.5	12.0	48.0	48.5	4.5	4~6
2	YCY XX1215	451215	45	35	≤550	3.7	4.7	4.8	12.2	12.5	15.0	15.5	1.0	4~6
3	YCY XX1219	061219L	75	70	≤350	3.7	5.2	5.5	12.5	13.0	19.0	19.5	1.7	3~4
4		061219H	90	80	≤320	3.7	6.4	6.5	12.0	12.5	19.0	19.5	1.9	4~6
5	YCYXX1221	041221	60	50	≤450	3.7	4.0	4.2	12.0	12.5	21.0	21.5	1.4	3~5
6		051221	80	70	≤380	3.7	5.0	5.2	12.0	12.5	21.0	21.5	1.7	4~6
7	YCYXX1225	381225	70	60	≤400	3.7	3.8	4.0	12.0	12.5	25.0	25.5	1.6	3~4
8		041225	80	70	≤350	3.7	4.0	4.2	12.0	12.5	25.0	25.5	1.7	3~4
9		051225L	100	85	≤320	3.7	4.7	4.8	12.2	12.5	25.0	25.5	1.9	4~6
10		051225H	110	100	≤280	3.7	5.3	5.5	12.2	12.5	25.0	25.5	2.6	3~4
11		061225	120	110	≤260	3.7	6.0	6.2	12.2	12.5	25.0	25.5	2.7	4~6
12	YCY XX1230	351230	85	80	≤350	3.7	3.5	3.7	12.0	12.5	30.0	30.5	1.9	3~4
13		551230	140	130	≤200	3.7	5.6	5.7	12.2	12.5	30.0	30.5	3.0	4~6
14	YCY XX1235	041235	120	100	≤260	3.7	4.0	4.2	12.0	12.5	35.0	35.5	2.7	3~4
15		451235	130	120	≤220	3.7	4.5	4.5	12.0	12.5	35.0	35.5	2.9	3~4
16		051235	150	150	≤180	3.7	5.2	5.3	12.2	12.5	35.0	35.5	3.2	4~6
17		551235	180	170	≤180	3.7	5.5	5.7	12.2	12.5	35.0	35.5	3.8	4~6
18		651235	200	180	≤150	3.7	6.5	6.7	12.2	12.5	35.0	35.5	4.8	4~6
19		071235	240	220	≤130	3.7	7.0	7.2	12.2	12.5	35.0	35.5	4.6	4~6
20	YCY XX1429	351429	100	90	≤300	3.7	3.5	3.7	14.0	14.5	29.0	29.5	2.4	4~6
21		041429	120	110	≤260	3.7	4.0	4.2	14.0	14.5	29.0	29.5	2.7	4~6
22		041429H	140	130	≤200	3.7	4.2	4.3	14.0	14.5	29.0	29.5	3.0	4~6

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
23	YCY XX1429	051429	150	140	≤180	3.7	5.0	5.2	14.0	14.5	29.0	29.5	3.2	4~6
24		551429	170	160	≤180	3.7	5.5	5.0	14.2	14.5	29.0	29.0	3.8	4~6
25	YCY XX1515	041515	50	40	≤520	3.7	4.0	4.2	15.0	15.5	15.0	15.5	1.1	5~7
26	YCY XX1518	451518	70	60	≤400	3.7	4.5	4.7	15.0	15.5	18.0	18.5	1.6	4~6
27	YCY XX1624	351624	100	90	≤300	3.7	3.5	3.7	16.0	16.5	24.0	24.0	2.4	6~8
28	YCY XX1630	381630	130	120	≤220	3.7	3.8	4.0	16.0	16.5	30.0	30.5	2.9	5~7
29		451630	160	150	≤170	3.7	4.2	4.5	16.0	16.5	30.0	30.5	3.5	5~7
30	YCY XX1640	351640	180	170	≤150	3.7	3.8	4.0	16.0	16.5	40.0	40.5	3.9	6~8
31	YCY XX1730	451730	170	160	≤180	3.7	4.5	4.7	17.0	17.5	29.5	30.0	3.8	7~9
32		551730	210	190	≤160	3.7	5.5	5.7	17.0	17.5	30.0	30.0	5.0	5~7
33		651730	270	250	≤120	3.7	6.5	6.5	17.0	17.5	30.0	30.0	5.6	4~6
34	YCY XX1745	351745	220	200	≤150	3.7	3.5	3.7	17.0	17.5	45.0	45.5	4.3	7~9
35	YCY XX1752	061752	400	380	≤90	3.7	5.5	6.0	17.0	17.5	52.0	52.5	8.0	4~6
36	YCY XX1830	321830	130	120	≤220	3.7	3.3	3.4	18.0	18.5	30.0	30.5	2.9	8~10
37		051830	230	210	≤130	3.7	5.1	5.2	18.0	18.0	30.0	30.5	4.4	6~8
38	YCY XX1842	031842	180	170	≤150	3.7	3.2	3.2	18.2	18.5	30.0	30.5	3.9	8~10
39		041842	250	240	≤120	3.7	4.2	4.3	18.0	18.5	42.0	42.5	4.8	7~9
40	YCY XX1845	351845	220	200	≤130	3.7	3.5	3.6	17.5	18.0	44.5	45.0	4.2	7~9
41		051845	380	360	≤100	3.7	5.0	5.2	18.2	18.5	45.0	45.5	7.8	6~8
42	YCY XX2024	042024	140	140	≤200	3.7	4.0	4.2	19.8	20.0	23.5	24.0	3.2	9~11
43	YCY XX2025	042025	150	150	≤180	3.7	4.0	4.2	20.0	20.5	25.0	25.5	3.4	9~11
44		422025H	180	170	≤150	3.7	4.3	4.4	20.0	20.5	25.0	25.5	3.9	9~11
45		052025	180	160	≤150	3.7	5.0	5.2	20.0	20.5	25.0	25.5	3.9	8~10
46		552025	240	200	≤150	3.7	5.5	5.7	20.2	20.5	25.0	25.5	4.6	8~10
47	YCY XX2030	382030	180	170	≤170	3.7	3.8	4.0	20.0	20.5	30.0	30.5	3.9	9~11

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
48	YCY XX2030	042030	200	180	≤150	3.7	4.0	4.2	20.0	20.5	30.0	30.5	4.8	9~11
49		052030	260	240	≤135	3.7	5.0	5.2	20.0	20.5	30.0	30.5	5.2	8~10
50		062030	300	280	≤110	3.7	6.0	6.2	20.0	20.5	30.0	30.5	6.0	7~9
51	YCY XX2035	042035	240	220	≤150	3.7	4.0	4.0	19.8	20.5	35.0	35.5	4.6	9~11
52		052035	320	300	≤100	3.7	5.0	5.2	20.0	20.5	35.0	35.5	6.4	8~10
53		532035	340	320	≤100	3.7	5.3	5.5	20.2	20.5	35.0	35.5	6.7	8~10
54	YCY XX2039	042039	270	250	≤120	3.7	4.0	4.2	20.0	20.5	39.0	39.5	5.4	9~11
55	YCY XX2048	042048	340	320	≤100	3.7	4.0	4.2	20.0	20.5	48.0	48.5	6.8	9~11
56	YCY XX2055	432055	450	430	≤80	3.7	4.3	4.5	20.3	20.5	55.0	55.5	9.0	9~11
57	YCY XX206	552060	620	600	≤70	3.7	5.5	5.7	20.0	20.5	60.0	60.5	12.8	7~9
58	YCY XX2234	582234	400	380	≤90	3.7	5.8	6.0	22.0	22.5	34.0	34.5	8.1	9~11
59	YCY XX2242	552242	480	460	≤80	3.7	5.5	5.7	22.5	23.0	42.0	42.5	9.0	10~12
60	YCY XX2248	532248	500	480	≤80	3.7	5.3	5.5	22.5	23.0	48.0	48.5	10.5	10~12
61	YCY XX2294	082294	1200	1150	≤50	3.7	6.2	6.5	21.5	22.0	92.0	93.0	24.0	6~8
62	YCY XX2328	042328	220	200	≤180	3.7	4.0	4.2	23.0	23.5	28.0	28.5	4.3	12~14
63	YCY XX2336	072336	500	500	≤80	3.7	7.0	7.2	23.0	23.5	36.0	36.5	10.5	9~11
64	YCY XX2448	042448	400	380	≤60	3.7	3.9	4.0	24.0	24.5	48.0	48.5	8.1	13~15
65	YCY XX2530	052530	320	300	≤150	3.7	5.0	5.2	25.0	25.5	30.0	30.5	6.8	13~15
66		062530	400	380	≤100	3.7	6.0	6.2	25.0	25.5	30.0	30.5	8.1	12~14
67		072530	420	400	≤100	3.7	7.0	7.2	25.2	25.5	30.0	30.5	8.3	11~13
68		102530	700	700	≤70	3.7	10.0	10.2	25.0	25.5	30.0	30.5	13.0	
69	YCY XX2535	042535	320	300	≤150	3.7	4.0	4.2	25.0	25.5	35.0	35.5	6.8	14~16
70		052535	400	380	≤100	3.7	5.0	5.2	25.0	25.5	35.0	35.5	8.1	13~15
71		062535	500	480	≤80	3.7	6.0	6.2	25.0	25.5	35.0	35.5	9.7	12~14
72		652535	500	480	≤80	3.7	6.4	6.5	25.0	25.5	35.0	35.5	10.0	12~14

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
73	YCY XX2540	062540	550	530	≤80	3.7	6.0	6.2	25.0	25.5	40.0	40.5	10.8	12~14
74	YCY XX2648	352648	400	380	≤100	3.7	3.5	3.7	26.0	26.5	48.0	48.5	8.2	15~17
75		482648	570	550	≤80	3.7	4.8	5.0	26.0	26.5	48.0	48.5	11.0	14~16
76		062648	800	750	≤50	3.7	6.0	6.0	26.0	26.5	48.0	48.5	16.0	13~15
77	YCY XX3040	043040	450	420	≤80	3.7	4.0	4.2	30.0	30.5	40.0	40.5	9.0	18~20
78		053040	560	540	≤80	3.7	5.0	5.2	30.0	30.5	40.0	40.5	10.8	16~18
79		523040	600	580	≤80	3.7	5.3	5.4	30.0	30.5	40.0	40.5	12.2	16~18
80		753040	850	820	≤60	3.7	7.3	7.5	30.0	30.5	40.0	40.5	16.5	15~17
81	YCY XX3048	043048	540	520	≤80	3.7	4.0	4.2	30.0	30.5	48.0	48.5	10.5	18~20
82		053048	720	700	≤60	3.7	5.0	5.2	30.0	30.5	48.0	48.5	14.0	17~19
83		063048	880	850	≤60	3.7	6.0	6.0	30.0	30.5	48.0	48.5	17.0	16~18
84		073048	1000	950	≤60	3.7	7.0	7.2	30.0	30.5	48.0	48.5	19.5	15~17
85		753048	1200	1050	≤60	3.7	7.5	7.8	30.0	30.5	48.0	48.5	21.5	14~16
86		083048	1200	1150	≤50	3.7	8.2	8.5	30.0	30.5	48.0	48.5	23.5	14~16
87	YCY XX3053	423053	640	620	≤80	3.7	4.2	4.4	30.0	30.5	53.0	53.5	12.5	18~20
88	YCY XX3155	053155	850	820	≤60	3.7	5.2	5.4	31.5	32.0	55.0	55.5	16.5	18~20
89	YCY XX3250	383250	600	580	≤80	3.7	3.8	4.0	32.0	32.5	50.0	50.5	12.2	20~22
90		063250	1000	950	≤50	3.7	6.0	6.2	32.0	32.5	50.0	50.5	19.5	18~20
91	YCY XX3347	053347	780	750	≤50	3.7	5.0	5.2	33.0	33.5	47.0	47.5	15.0	21~23
92	YCY XX3365	083365	1800	1800	≤50	3.7	7.8	8.0	33.0	33.5	65.0	65.5	35.0	15~17
93		103365	2200	2200	≤40	3.7	9.8	10.0	33.0	33.5	65.0	65.5	42.0	13~15
94	YCY XX3370	553370	1200	1150	≤50	3.7	5.3	5.5	33.0	33.5	70.0	70.5	23.5	19~21
95	YCY XX3436	033436	320	300	≤100	3.7	3.1	3.2	34.2	34.5	36.0	36.5	6.8	23~25
96		363436	380	360	≤80	3.7	3.5	3.6	34.5	35.0	36.0	36.5	7.5	22~24
97		553436	650	620	≤60	3.7	5.5	5.7	34.0	34.5	36.0	36.5	12.8	20~22

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
98	YCY XX3448	053448	820	800	≤60	3.7	5.0	5.0	34.5	35.0	48.0	48.5	16.0	21~23
99		063448	850	820	≤60	3.7	5.8	6.0	34.0	34.5	48.0	48.5	17.0	20~22
100		083448	1250	1200	≤50	3.7	7.8	8.0	34.0	34.5	48.0	48.5	24.5	18~20
101		103448	1600	1500	≤50	3.7	9.3	9.5	34.5	35.0	49.8	50.0	31.0	16~18
102	YCY XX3450	383450	650	620	≤60	3.7	3.8	4.0	34.0	34.5	50.0	50.5	12.8	22~24
103		053450	850	800	≤60	3.7	5.0	5.2	34.0	34.5	50.0	50.5	16.8	21~23
104		063450L	850	850	≤60	3.7	5.6	5.8	34.0	34.5	50.0	50.5	17.8	20~22
105		063450	1100	1050	≤60	3.7	6.0	6.2	34.0	34.5	50.0	50.5	21.5	20~22
106		083450	1250	1200	≤60	3.7	7.8	8.0	34.2	34.5	50.0	50.5	24.5	18~20
107		853450	1500	1400	≤50	3.7	8.5	8.8	34.0	34.5	50.0	50.5	29.0	17~19
108		103450	1800	1700	≤50	3.7	10.3	10.8	34.5	35.0	50.0	50.5	35.0	15~17
109	YCY XX3465	383465	850	820	≤50	3.7	3.8	4.0	34.0	34.5	65.0	65.5	16.8	22~24
110		043465	800	780	≤50	3.7	4.0	4.2	34.0	34.5	65.0	65.5	16.0	22~24
111		053465	1150	1050	≤50	3.7	5.0	5.2	34.2	34.5	65.0	65.5	25.0	21~23
112		063465	1350	1300	≤50	3.7	6.0	6.2	34.0	34.5	65.0	65.5	26.0	20~22
113	YCY XX3549	753549	1350	1300	≤50	3.7	7.4	7.6	35.0	35.5	49.0	49.5		
114	YCY XX3555	033555	520	500	≤60	3.7	3.0	3.1	35.2	35.5	55.0	55.5	10.2	21.5~23.5
115	YCY XX3562	383562	800	780	≤60	3.7	3.8	4.0	35.0	35.5	62.0	62.5	16.0	23~25
116		423562	880	840	≤60	3.7	4.2	4.4	35.0	35.5	62.0	62.0	17.2	23~25
117		053562	1050	1000	≤50	3.7	5.0	5.2	35.0	35.5	62.0	62.5	20.5	22~24
118		653562	1400	1350	≤50	3.7	6.5	6.7	35.0	35.5	62.0	62.5	27.0	20~22
119	YCY XX3680	653680	1750	1650	≤50	3.7	6.5	6.7	36.0	36.5	80.0	80.5	34.0	21~23
120	YCY XX3740	573740	800	780	≤50	3.7	5.7	5.9	37.0	37.5	40.5	41.0	16.0	23~25
121		073740	1000	900	≤50	3.7	7.0	7.0	37.5	38.0	41.0	41.5	19.5	22~24
122	YCY XX3742	423742L	600	580	≤50	3.7	4.2	4.4	37.0	37.5	42.0	42.5	12.2	25~27

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
123	YCY XX3742	423742	620	600	≤50	3.7	4.3	4.4	37.0	37.5	42.0	42.5	12.5	25~27
124	YCY XX3759	053759HT	1100	1000	≤50	3.7	5.0	5.5	37.0	37.5	59.0	59.5	22.5	24~26
125		053759	1200	1100	≤50	3.7	5.0	5.2	37.0	37.5	59.0	59.5	23.0	24~26
126		583759HT	1300	1200	≤50	3.7	5.8	6.5	37.0	37.5	59.0	59.5	26.0	23~25
127		583759	1400	1300	≤50	3.7	5.8	6.0	37.0	37.5	59.0	59.5	27.0	23~25
128		YCY XX3767	073767L	1500	1450	≤50	3.7	6.5	6.7	37.0	37.5	67.0	67.5	29.5
129	073767		1800	1700	≤50	3.7	7.0	7.2	37.0	37.5	67.0	67.5	35.0	22~24
130	YCY XX3954	063954	1300	1200	≤50	3.7	5.8	6.0	39.0	39.5	54.0	54.5	25.0	25~27
131	YCY XX4050	554050	1100	1000	≤50	3.7	5.5	5.7	40.0	40.5	50.0	50.5	21.5	27~29
132		654050	1400	1300	≤50	3.7	6.6	6.7	40.0	40.5	50.0	50.5	27.0	26~28
133	YCY XX4292	064292	2500	2400	≤50	3.7	6.0	6.2	42.0	42.5	92.0	92.5	48.5	28~30
134	YCY XX4540	054540	900	850	≤50	3.7	5.0	5.0	45.0	45.5	40.0	40.5	17.5	7~9
135	YCY XX4545	484545	1000	950	≤50	3.7	4.8	5.0	45.5	46.0	45.0	45.5	20.0	10~12
136	YCY XX4550	324550	650	650	≤50	3.7	3.2	3.4	45.0	45.5	50.0	50.5	12.5	28~32
137		044550	900	900	≤50	3.7	4.1	4.2	45.0	45.5	50.0	50.5	17.5	30~32
138		064550	1400	1350	≤50	3.7	6.0	6.2	45.0	45.5	50.0	50.5	27.0	22~24
139	YCY XX4570	044570	1200	1150	≤50	3.7	4.0	4.2	45.0	45.5	70.0	70.5	23.0	33~35
140	YCY XX45131	0845131	5100	5100	≤50	3.7	7.5	8.0	45.0	45.5	131.0	131.5	98.8	25~27
141	YCY XX4854	434854	1100	1100	≤50	3.7	4.3	4.5	48.0	48.5	54.0	54.5	21.5	
142		554854	1500	1450	≤50	3.7	5.5	5.7	48.0	48.5	54.0	55.0	29.5	27~29
143		794854	2100	2000	≤50	3.7	7.9	8.1	48.5	49.0	54.5	55.0	40.0	27~29
144	YCY XX48120	3848120	2500	2350	≤50	3.7	3.8	4.0	48.0	48.5	120.0	121.0	48.0	23~25
145	YCY XX48130	0448130	2600	2500	≤50	3.7	4.0	4.2	48.0	48.5	130.0	131.0	50.0	27~29
146	YCY XX5057	555057	1850	1800	≤50	3.7	5.7	5.9	50.0	50.5	57.0	57.5	35.5	23~25
147	YCY XX5060	055060L	1300	1200	≤50	3.7	4.5	4.7	49.5	50.0	59.5	60.0	23.0	34~36

序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
148	YCY XX5060	055060X	1500	1450	≤50	3.7	5.0	5.2	50.0	50.5	60.0	60.5	29.5	33~35
149	YCY XX5065	055065	1700	1600	≤50	3.7	5.0	5.2	50.0	50.5	64.0	65.0	33.0	33~35
150	YCY XX5070	055070	1800	1700	≤50	3.7	4.8	5.0	49.5	50.0	70.0	70.5	35.0	29~31
151	YCY XX5073	455073	1800	1750	≤50	3.7	4.7	4.9	50.5	51.0	73.0	73.5	35.0	26~28
152		545073	2000	1900	≤50	3.7	5.5	5.6	50.5	51.0	73.0	73.5	38.5	29~30
153	YCY XX5080	035080	1200	1100	≤50	3.7	3.1	3.2	49.5	50.0	80.0	80.5	23.0	26~28
154		055080	2000	1900	≤50	3.7	5.0	5.2	50.0	50.5	80.0	80.5	38.0	28~30
155		065080	2400	2300	≤50	3.7	6.0	6.2	50.0	50.5	80.0	80.5	46.0	33~35
156	YCY XX5085	045085	1700	1600	≤50	3.7	4.0	4.2	50.0	50.5	85.0	85.5	33.0	29~31
157		555085	2200	2150	≤50	3.7	5.4	5.5	50.0	50.0	85.0	85.5	42.0	35~37
158	YCY XX5090	055090	2500	2450	≤50	3.7	5.2	5.3	50.0	50.5	90.0	90.0	48.0	33~35
159	YCY XX50100	0550100	2500	2400	≤50	3.7	5.0	5.2	50.0	50.5	100.0	100.5	48.0	33~35
160		0650100	3000	2900	≤50	3.7	6.0	6.2	50.0	50.5	100.0	100.5	58.0	22~24
161		0850100	4100	4000	≤50	3.7	7.5	8.0	50.0	50.5	100.0	100.5	77.0	22~24
162	YCY XX5158	455158	1300	1250	≤50	3.7	4.5	4.7	51.0	51.5	58.0	58.5	25.0	22~24
163	YCY XX5256	055256	1400	1350	≤50	3.7	5.0	5.0	52.0	52.5	56.0	56.5	27.0	15~17
164		545256L	1500	1400	≤50	3.7	5.3	5.4	52.0	52.5	56.0	56.5	29.0	15~17
165		545256	1700	1600	≤50	3.7	5.5	5.6	52.5	53.0	56.0	56.5	33.0	15~17
166	YCY XX5376	555376	2300	2200	≤50	3.7	5.6	5.8	53.0	53.5	76.5	77.0	44.0	33~35
167	YCY XX5575	085575	3400	3200	≤40	3.7	7.5	7.8	55.0	55.5	75.0	75.5	65.0	34~36
168	YCY XX5585	045585	1900	1850	≤50	3.7	4.0	4.2	55.0	55.5	85.0	85.5	37.0	23~25
169	YCY XX5590	035590L	1200	1150	≤50	3.7	3.1	3.2	55.0	55.5	90.0	90.5	23.0	18~20
170		035590	1500	1400	≤50	3.7	3.2	3.3	55.0	55.5	90.0	90.5	29.0	20~22
171	YCY XX5766	555766	2000	1900	≤50	3.7	5.5	5.7	57.0	57.5	66.0	66.5	38.0	31~33
172	YCY XX6168	606168	2500	2450	≤50	3.7	6.0	6.2	61.0	61.5	68.0	68.0	44.0	22~24



序号	电池系列	典型型号	典型容量	最小容量	内阻	标称电压	外形尺寸/mm(仅为单体电池尺寸)						重量	极耳间距
			/mAh	/mAh	/mΩ	/V	厚度	Max	宽度	Max	长度	Max	典型g	mm
173	YCY XX67100	0567100	3400	3300	≤50	3.7	4.8	5.0	67.0	67.5	100.0	100.5	65.0	24~26
174		0667100	4100	3900	≤50	3.7	6.0	6.2	67.0	67.5	100.0	100.5	77.0	30~32
175	YCY XX6842	786842	2300	2200	≤50	3.7	7.8	8.0	68.5	69.0	42.5	43.0	44.0	14~16
176	YCY XX3048	063048	620	550	≤70	3.7	6.1	6.2	30.0	30.5	48.0	48.5	13.5	14~16
177		073048	800	750	≤32	3.7	7.0	7.2	30.0	30.5	48.0	48.5	19.5	10~12
178		103048	1100	1050	≤50	3.7	10.0	10.2	30.0	30.5	48.5	49.0	25.0	9~11
179	YCY XX2664	092664	1350	1300	≤50	3.7	9.0	9.2	26.0	26.5	64.0	64.5	31.0	15~17
180	YCY XX52103	6052103	3200	3150	≤50	3.7	6.0	6.2	52.0	52.5	103.0	103.5	65.0	15~17

“XX”表示电池的厚度，并可按照客户要求定做特定厚度的电池，一般情况下XX的范围是：3~6mm，3mm以下的电芯目前不开发，6mm以上的电池需要开双坑模具，有些模具比较小的5mm厚度以上就要双坑模具，其它未写型号请与相关业务人员联系。